

SAFETY DATA SHEET

Floorcoat FC24 - All versions

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Floorcoat FC24 - All versions

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

PC-PNT-2 Professional treatment of wooden floors, indoors.

Restricted to professional users.

Use descriptors (REACH)

Sectors of use	Description
SU 19	Building and construction work
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product category	Description
PC 9a	Coatings and Paints, Fillers, Putties, Thinners
Process category	Description
PROC 10	Roller application or brushing
Environmental release category	Description
ERC 8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Floorcoat A/S
 Egestubben 4C
 DK-5270 Odense N
 Denmark
 Tel: +45 6618 0306
 Fax: +45 6618 4346
www.floorcoat.eu

Contact person

Lars Olsen

E-mail

info@tiptopslib.dk

Revision

16/04/2024

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Not applicable.

Precautionary statement(s)

General

-

Prevention

-

Response

-

Storage

-

Disposal

-

Hazardous substances

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isoth

Additional labelling

EUH208, Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isoth. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

VOC

VOC content: 40-50 g/L

MAXIMUM VOC CONTENT (Phase II, category A/i (WB): 140 g/L)

2.3. Other hazards**Additional warnings**

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
(2-methoxymethylethoxy)propanol	CAS No.: 34590-94-8 EC No.: 252-104-2 UK-REACH: Index No.:	3-5%		[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Not applicable.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

HDPE

Storage temperature

Room temperature 18 to 23°C (Storage on stock, 3 to 8°C)

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

(2-methoxymethylethoxy)propanol

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 308

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

2-(2-butoxyethoxy)ethanol

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 67,5

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m³): 101,2

2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Long term exposure limit (8 hours) (ppm): 25

Long term exposure limit (8 hours) (mg/m³): 123

Short term exposure limit (15 minutes) (ppm): 50

Short term exposure limit (15 minutes) (mg/m³): 246

Annotations:

BMVG = Biological Monitoring Guidance Value exists

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isoth

Duration:	Route of exposure:	DNEL:
Long term - Local effects - General population	Inhalation	20 µg/m ³
Long term - Local effects - Workers	Inhalation	20 µg/m ³
Short term - Local effects - General population	Inhalation	40 µg/m ³
Short term - Local effects - Workers	Inhalation	40 µg/m ³
Long term - Systemic effects - General population	Oral	90 µg/kgbw/day
Short term - Systemic effects - General population	Oral	110 µg/kgbw/day

(2-methoxymethylethoxy)propanol

Duration:	Route of exposure:	DNEL:
Long term - Systemic effects - General population	Dermal	121 mg/kg bwt/day
Long term - Systemic effects - General population	Dermal	121 mg/kg bw/day
Long term - Systemic effects - Workers	Dermal	283 mg/kg bwt/day
Long term - Systemic effects - Workers	Dermal	283 mg/kg bw/day
Long term - Systemic effects - General population	Inhalation	37.2 mg/m ³
Long term - Systemic effects - Workers	Inhalation	308 mg/m ³
Long term - Systemic effects - Workers	Inhalation	308 mg/m ³

Long term - Systemic effects - General population	Oral	36 mg/kg bwt/day
Long term - Systemic effects - General population	Oral	36 mg/kg bw/day
1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one		
Duration:	Route of exposure:	DNEL:
Long term - Systemic effects - General population	Dermal	345 µg/kgbw/day
Long term - Systemic effects - Workers	Dermal	0.966 mg/kg bw/day
Long term - Systemic effects - Workers	Dermal	966 µg/kgbw/day
Long term - Systemic effects - General population	Inhalation	1.2 mg/m ³
Long term - Systemic effects - Workers	Inhalation	2634-33-5
Long term - Systemic effects - Workers	Inhalation	6.81 mg/m ³
2-(2-butoxyethoxy)ethanol		
Duration:	Route of exposure:	DNEL:
Long term - Local effects - Workers	Dermal	low hazard (no threshold derived)
Long term - Local effects - Workers	Inhalation	67.5 mg/m ³
Long term - Local effects - Workers	Inhalation	67.5 mg/m ³
Short term - Local effects - Workers	Inhalation	101.2 mg/m ³
Long term - Systemic effects - General population	Oral	6.25 mg/kg bw/day
2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve		
Duration:	Route of exposure:	DNEL:
Long term - Systemic effects - Workers	Dermal	low hazard (no threshold derived)
Long term - Systemic effects - General population	Inhalation	59 mg/m ³
Long term - Systemic effects - Workers	Inhalation	98 mg/m ³
Long term - Systemic effects - Workers	Inhalation	98 mg/m ³
Short term - Local effects - General population	Inhalation	147 mg/m ³
Short term - Local effects - Workers	Inhalation	246 mg/m ³
Short term - Systemic effects - General population	Inhalation	426 mg/m ³
Short term - Systemic effects - Workers	Inhalation	1091 mg/m ³
Long term - Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term - Systemic effects - General population	Oral	26.7 mg/kg bw/day
2-methyl-2H-isothiazol-3-one		
Duration:	Route of exposure:	DNEL:
Long term - Local effects - General population	Inhalation	21 µg/m ³
Long term - Local effects - Workers	Inhalation	21 µg/m ³
Short term - Local effects - General population	Inhalation	43 µg/m ³
Short term - Local effects - Workers	Inhalation	43 µg/m ³
Long term - Systemic effects - General population	Oral	27 µ/kgbw/day
Short term - Systemic effects - General population	Oral	53 µ/kgbw/day

PNEC

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isoth

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3.39 µg/L
Freshwater sediment		27 µ/kg
Intermittent release (freshwater)		3.39 µg/L
Intermittent release (marine water)		3.39 µg/L

Marine water		3.39 µg/L
Marine water sediment		27 µg/kg
Sewage treatment plant		230 µg/L
Soil		10 µg/kg
(2-methoxymethylethoxy)propanol		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		19 mg/L
Freshwater		19 mg/L
Freshwater sediment		70.2 mg/kg
Intermittent release (freshwater)		190 mg/L
Marine water		1,9 mg/L
Marine water		1.9 mg/L
Marine water sediment		7.02 mg/kg
Sewage treatment plant		4.168 g/L
Soil		2.74 mg/kg
1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Continuous	4.03 µg/L
Freshwater		4.03 µg/L
Freshwater sediment		49.9 µg/kg
Intermittent release (freshwater)		1.1 µg/L
Intermittent release (marine water)		110 ng/L
Marine water	Continuous	0.403 µg/L
Marine water		403 ng/L
Marine water sediment		4.99 µg/kg
Sewage treatment plant		1.03 mg/L
Soil		3 mg/kg
2-(2-butoxyethoxy)ethanol		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Continuous	1,1 mg/L
Freshwater		1.1 mg/L
Freshwater sediment		4.4 mg/kg
Intermittent release (freshwater)		11 mg/L
Marine water	Continuous	0.11 mg/L
Marine water		110 µg/L
Marine water sediment		440 µg/kg
Predators		56 mg/kg
Soil		320 µg/kg
2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Continuous	8.8 mg/L
Freshwater		8.8 mg/L
Freshwater sediment		34.6 mg/kg
Intermittent release (freshwater)		26.4 mg/L
Marine water	Continuous	0.88 mg/L
Marine water		880 µg/L

Marine water sediment	3.46 mg/kg	
Predators	20 mg/kg	
Sewage treatment plant	463 mg/L	
Soil	2.33 mg/kg	
2-methyl-2H-isothiazol-3-one		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		3.39 µg/L
Intermittent release (freshwater)		3.39 µg/L
Intermittent release (marine water)		3.39 µg/L
Marine water		3.39 µg/L
Sewage treatment plant		230 µg/L
Soil		47.1 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
No special when used as intended.			

Skin protection

Recommended	Type/Category	Standards
No special when used as intended	-	-



Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388



Eye protection

Work situation	Type	Standards
Professional use	Wear safety glasses with side shields.	EN166

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

White

Odour / Odour threshold

Characteristic

pH

7-9

Density (g/cm³)

0,90-1,10 (20 °C)

Kinematic viscosity

No data available

Particle characteristics

Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C)

Not applicable - product is a liquid

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

100

Vapour pressure

No data available

Relative vapour density

No data available

Decomposition temperature (°C)

No data available

Data on fire and explosion hazards

Flash point (°C)

>100

Flammability (°C)

No data available

Auto-ignition temperature (°C)

No data available

Lower and upper explosion limit (% v/v)

Not applicable

Solubility

Solubility in water

Completely soluble

n-octanol/water coefficient (LogK_{ow})

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Evaporation rate (n-butylacetate = 100)

No data available

VOC (g/L)

40-50

Other physical and chemical parameters

No data available.

Oxidizing properties

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Species: Rabbit

Route of exposure: Dermal

Test: LD50

Result: 2270 mg/kg .

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Species: Rat

Route of exposure: Oral

Test: LD50

Result: 1746 mg/kg .

Product/substance 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one

Species: Rat

Route of exposure: Oral

Test: LD50

Result: 1193 mg/kg .

Product/substance 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one

Species: Rat

Route of exposure: Dermal

Test: LD50

Result: 4115 mg/kg .

Product/substance 2-methyl-2H-isothiazol-3-one

Species: Rat

Route of exposure: Oral

Test: LD50

Result: 285 mg/kg .

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Long term effects**

None known.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information**12.1. Toxicity**

Product/substance 2-(2-butoxyethoxy)ethanol

Species: Algae

Duration: 72 hours

Test: EC50

Result: 1101 mg/L ·

Product/substance 2-(2-butoxyethoxy)ethanol

Species: Fish

Duration: 72 hours

Test: LC50

Result: 2400 mg/L ·

Product/substance 2-(2-butoxyethoxy)ethanol

Species: Daphnia

Duration: 48 hours

Test: EC50

Result: >100 mg/L ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Species: Algae

Duration: 72 hours

Test: EC50

Result: 911 mg/L ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Species: Fish

Duration: 96 hours

Test: LC50

Result: 1474 mg/L ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Species: Daphnia

Duration: 48 hours

Test: EC50

Result: 1550 mg/L ·

Product/substance reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isoth

Species: Daphnia

Duration: 48 hours

Test: EC50

Result: 0,126 mg/L ·

Product/substance reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isoth

Species: Fish

Duration: 96 hours

Test:	EC50
Result:	0,188 mg/L ·
Product/substance	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazolin-3-one
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	0,027 mg/L ·
Product/substance	1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	2,18 mg/L ·
Product/substance	1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	2,94 mg/L ·
Product/substance	1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	0,11 mg/L ·
Product/substance	2-methyl-2H-isothiazol-3-one
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	4,77 mg/L ·
Product/substance	2-methyl-2H-isothiazol-3-one
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	0,93 mg/L ·

12.2. Persistence and degradability

Product/substance	2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve
Conclusion:	Readily biodegradable

12.3. Bioaccumulative potential

Product/substance	2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve
Conclusion:	No potential for bioaccumulation

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packing

EWC code

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

REACH, Annex XVII

2-(2-butoxyethoxy)ethanol is subject to restrictions, UK-REACH annex XVII (entry 55).

Additional information

Not applicable.

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

The full text of identified uses as mentioned in section 1

SU 19 = Building and construction work

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PROC 10 = Roller application or brushing

PC 9a = Coatings and Paints, Fillers, Putties, Thinners

ERC 8c = Wide dispersive indoor use resulting in inclusion into or onto a matrix

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

Not applicable.

The safety data sheet is validated by

AG

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en