

## SAFETY DATA SHEET

## Floorcoat FC82 - All versions

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## ▼ Trade name

Floorcoat FC82 - All versions

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## ▼ Relevant identified uses of the substance or mixture

PC-PNT-2 Professional treatment of wooden floors, indoors.

Restricted to professional users.

## Use descriptors (REACH)

Sectors of use	Description
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 19	Building and construction work
Product category	Description
PC 9a	Coatings and Paints, Fillers, Putties, Thinners
Process category	Description
PROC 10	Roller application or brushing
Environmental release category	Description
ERC 8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

## Uses advised against

None known.

## 1.3. Details of the supplier of the safety data sheet

## Company and address

**Floorcoat A/S**  
 Egestubben 4C  
 DK-5270 Odense N  
 Denmark  
 Tel: +45 6618 0306  
 Fax: +45 6618 4346  
[www.floorcoat.eu](http://www.floorcoat.eu)

## Contact person

Lars Olsen

## E-mail

[info@tiptopslib.dk](mailto:info@tiptopslib.dk)

## Revision

23/09/2024

## SDS Version

5.0

## Date of previous version

26/04/2023 (4.0)

## 1.4. ▼ Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

### 2.2. Label elements

#### Hazard pictogram(s)

Not applicable.

#### Signal word

Not applicable.

#### Hazard statement(s)

Not applicable.

#### Precautionary statement(s)

##### General

-

##### Prevention

-

##### Response

-

##### Storage

-

##### Disposal

-

#### Hazardous substances

1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isoth

#### Additional labelling

EUH208, Contains 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isoth. May produce an allergic reaction.

EUH210, Safety data sheet available on request.

#### VOC

VOC content: 80-90 g/L

MAXIMUM VOC CONTENT (Phase II, category A/j (WB): 140 g/L)

### 2.3. Other hazards

#### ▼ Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
(2-methoxymethylethoxy)propanol	CAS No.: 34590-94-8 EC No.: 252-104-2 UK-REACH: Index No.:	3-5%		[1]
2-butoxyethanol; ethylene glycol monobutyl ether; 2-butoxyethanol; ethylene glycol monobutyl ether; butyl cellosolve	CAS No.: 111-76-2 EC No.: 203-905-0 UK-REACH: Index No.: 603-014-00-0	3-5%	Acute Tox. 4, H302 (ATE: 1200.00 mg/kg) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 3, H331	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

**Other information**

[1] European occupational exposure limit.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

**Inhalation**

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

**Skin contact**

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

**▼ Eye contact**

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

**Ingestion**

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

**Burns**

Not applicable.

**4.2. Most important symptoms and effects, both acute and delayed**

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

**4.3. ▼ Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**Information to medics**

Bring this safety data sheet or the label from this product.

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

Not applicable.

**5.2. Special hazards arising from the substance or mixture**

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

**5.3. Advice for firefighters**

Fire fighters should wear appropriate personal protective equipment.

**SECTION 6: Accidental release measures****6.1. ▼ Personal precautions, protective equipment and emergency procedures**

Contaminated areas may be slippery.

**6.2. Environmental precautions**

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

**6.3. ▼ Methods and material for containment and cleaning up**

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

### SECTION 7: Handling and storage

#### 7.1. ▼Precautions for safe handling

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

##### Recommended storage material

Always store in containers of the same material as the original container.

##### Storage conditions

Room temperature 18 to 23°C (Storage on stock, 3 to 8°C)

##### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

(2-methoxymethylethoxy)propanol

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 308

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Long term exposure limit (8 hours) (ppm): 25

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 123

Short term exposure limit (15 minutes) (ppm): 50

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 246

Annotations:

BMVG = Biological Monitoring Guidance Value exists

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

#### DNEL

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isoth

Duration:	Route of exposure:	DNEL:
Long term - Local effects - General population	Inhalation	20 µg/m <sup>3</sup>
Long term - Local effects - Workers	Inhalation	20 µg/m <sup>3</sup>
Short term - Local effects - General population	Inhalation	40 µg/m <sup>3</sup>
Short term - Local effects - Workers	Inhalation	40 µg/m <sup>3</sup>
Long term - Systemic effects - General population	Oral	90 µg/kgbw/day
Short term - Systemic effects - General population	Oral	110 µg/kgbw/day

(2-methoxymethylethoxy)propanol

Duration:	Route of exposure:	DNEL:
Long term - Systemic effects - General population	Dermal	121 mg/kg bwt/day
Long term - Systemic effects - General population	Dermal	121 mg/kg bw/day

Long term - Systemic effects - Workers	Dermal	283 mg/kg bwt/day
Long term - Systemic effects - Workers	Dermal	283 mg/kg bw/day
Long term - Systemic effects - General population	Inhalation	37.2 mg/m <sup>3</sup>
Long term - Systemic effects - Workers	Inhalation	308 mg/m <sup>3</sup>
Long term - Systemic effects - Workers	Inhalation	308 mg/m <sup>3</sup>
Long term - Systemic effects - General population	Oral	36 mg/kg bwt/day
Long term - Systemic effects - General population	Oral	36 mg/kg bw/day

## 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one

<b>Duration:</b>	<b>Route of exposure:</b>	<b>DNEL:</b>
Long term - Systemic effects - General population	Dermal	345 µg/kgbw/day
Long term - Systemic effects - Workers	Dermal	0.966 mg/kg bw/day
Long term - Systemic effects - Workers	Dermal	966 µg/kgbw/day
Long term - Systemic effects - General population	Inhalation	1.2 mg/m <sup>3</sup>
Long term - Systemic effects - Workers	Inhalation	2634-33-5
Long term - Systemic effects - Workers	Inhalation	6.81 mg/m <sup>3</sup>

## 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

<b>Duration:</b>	<b>Route of exposure:</b>	<b>DNEL:</b>
Long term - Systemic effects - Workers	Dermal	low hazard (no threshold derived)
Long term - Systemic effects - General population	Inhalation	59 mg/m <sup>3</sup>
Long term - Systemic effects - Workers	Inhalation	98 mg/m <sup>3</sup>
Long term - Systemic effects - Workers	Inhalation	98 mg/m <sup>3</sup>
Short term - Local effects - General population	Inhalation	147 mg/m <sup>3</sup>
Short term - Local effects - Workers	Inhalation	246 mg/m <sup>3</sup>
Short term - Systemic effects - General population	Inhalation	426 mg/m <sup>3</sup>
Short term - Systemic effects - Workers	Inhalation	1091 mg/m <sup>3</sup>
Long term - Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term - Systemic effects - General population	Oral	26.7 mg/kg bw/day

## PNEC

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isoth

<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		3.39 µg/L
Freshwater sediment		27 µg/kg
Intermittent release (freshwater)		3.39 µg/L
Intermittent release (marine water)		3.39 µg/L
Marine water		3.39 µg/L
Marine water sediment		27 µg/kg
Sewage treatment plant		230 µg/L
Soil		10 µg/kg

## (2-methoxymethylethoxy)propanol

<b>Route of exposure:</b>	<b>Duration of Exposure:</b>	<b>PNEC:</b>
Freshwater		19 mg/L
Freshwater		19 mg/L
Freshwater sediment		70.2 mg/kg
Intermittent release (freshwater)		190 mg/L
Marine water		1,9 mg/L

Marine water	1.9 mg/L
Marine water sediment	7.02 mg/kg
Sewage treatment plant	4.168 g/L
Soil	2.74 mg/kg

## 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Continuous	4.03 µg/L
Freshwater		4.03 µg/L
Freshwater sediment		49.9 µg/kg
Intermittent release (freshwater)		1.1 µg/L
Intermittent release (marine water)		110 ng/L
Marine water	Continuous	0.403 µg/L
Marine water		403 ng/L
Marine water sediment		4.99 µg/kg
Sewage treatment plant		1.03 mg/L
Soil		3 mg/kg

## 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Continuous	8.8 mg/L
Freshwater		8.8 mg/L
Freshwater sediment		34.6 mg/kg
Intermittent release (freshwater)		26.4 mg/L
Marine water	Continuous	0.88 mg/L
Marine water		880 µg/L
Marine water sediment		3.46 mg/kg
Predators		20 mg/kg
Sewage treatment plant		463 mg/L
Soil		2.33 mg/kg

## 8.2. ▼Exposure controls

Apply general control to prevent unnecessary exposure

## General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

## Exposure scenarios

There are no exposure scenarios implemented for this product.

## ▼Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

## ▼Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

## ▼Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

## Measures to avoid environmental exposure

No specific requirements.

## Individual protection measures, such as personal protective equipment

## Generally

Use only UKCA marked protective equipment.

## Respiratory Equipment

Type	Class	Colour	Standards
Respiratory protection is not needed in the event of adequate	-	-	-

Type	Class	Colour	Standards
ventilation			
<b>Skin protection</b>			
Recommended	Type/Category		Standards
Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.			
<b>Hand protection</b>			
Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388
			
<b>Eye protection</b>			
Work situation	Type		Standards
Professional use	Face shield alternatively safety glasses with side shields.	EN166	

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

White

#### Odour / Odour threshold

Characteristic

#### pH

7-9

#### Density (g/cm<sup>3</sup>)

1,05-1,10 (20 °C)

#### Kinematic viscosity

No data available

#### Particle characteristics

Not applicable - product is a liquid

#### Phase changes

##### Melting point/Freezing point (°C)

No data available

##### Softening point/range (°C)

Does not apply to liquids.

##### Boiling point (°C)

No data available

##### Vapour pressure

No data available

##### Relative vapour density

No data available

##### Decomposition temperature (°C)

No data available

#### Data on fire and explosion hazards

##### Flash point (°C)

>100

##### Flammability (°C)

No data available

##### Auto-ignition temperature (°C)

No data available

▼ Lower and upper explosion limit (% v/v)

No relevant or available data due to the nature of the product.

**Solubility**

**Solubility in water**

Completely soluble

▼ n-octanol/water coefficient (LogKow)

No relevant or available data due to the nature of the product.

▼ Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

**9.2. Other information**

**Evaporation rate (n-butylacetate = 100)**

No data available

**VOC (g/L)**

80-90

**Other physical and chemical parameters**

No data available.

**Oxidizing properties**

No data available

## SECTION 10: Stability and reactivity

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

The product is stable under the conditions, noted in section 7 "Handling and storage".

**10.3. Possibility of hazardous reactions**

None known.

**10.4. Conditions to avoid**

None known.

**10.5. Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

**10.6. Hazardous decomposition products**

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Species: Rabbit

Route of exposure: Dermal

Test: LD50

Result: 2270 mg/kg .

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Species: Rat

Route of exposure: Oral

Test: LD50

Result: 1746 mg/kg .

Product/substance 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one

Species: Rat

Route of exposure: Oral

Test: LD50

Result: 1193 mg/kg .

Product/substance 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one

Species: Rat

Route of exposure: Dermal

Test: LD50  
 Result: 4115 mg/kg ·

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

Based on available data, the classification criteria are not met.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Long term effects

None known.

#### ▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

#### Other information

2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve has been classified by IARC as a group 3 carcinogen.

## SECTION 12: Ecological information

### 12.1. Toxicity

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Species: Algae

Duration: 72 hours

Test: EC50

Result: 911 mg/L ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Species: Fish

Duration: 96 hours

Test: LC50

Result: 1474 mg/L ·

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl ether;butyl cellosolve

Species: Daphnia

Duration: 48 hours

Test: EC50

Result: 1550 mg/L ·

Product/substance 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one

Species: Fish

Duration: 96 hours

Test: LC50

Result: 2,18 mg/L ·

Product/substance 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one

Species: Daphnia  
 Duration: 48 hours  
 Test: EC50  
 Result: 2,94 mg/L ·

Product/substance 1,2-benzisothiazol-3(2H)-one;1,2-benzisothiazolin-3-one  
 Species: Algae  
 Duration: 72 hours  
 Test: EC50  
 Result: 0,11 mg/L ·

Product/substance reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isoth  
 Species: Daphnia  
 Duration: 48 hours  
 Test: EC50  
 Result: 0,126 mg/L ·

Product/substance reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isoth  
 Species: Fish  
 Duration: 96 hours  
 Test: EC50  
 Result: 0,188 mg/L ·

Product/substance reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isoth  
 Species: Algae  
 Duration: 72 hours  
 Test: EC50  
 Result: 0,027 mg/L ·

## 12.2. ▼ Persistence and degradability

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl  
 ether;butyl cellosolve  
 Conclusion: Readily biodegradable

## 12.3. ▼ Bioaccumulative potential

Product/substance 2-butoxyethanol; ethylene glycol monobutyl ether;2-butoxyethanol;ethylene glycol monobutyl  
 ether;butyl cellosolve  
 Conclusion: No potential for bioaccumulation

## 12.4. Mobility in soil

No data available.

## 12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

## 12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

## 12.7. Other adverse effects

None known.

## SECTION 13: Disposal considerations

### 13.1. ▼ Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*)

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

#### ▼ EWC code

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

#### ▼ Contaminated packing

#### ▼ EWC code

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

## SECTION 14: Transport information

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-
IMDG	-	-	-	-	-
IATA	-	-	-	-	-

\* Packing group

\*\* Environmental hazards

**Additional information**

Not dangerous goods according to ADR, IATA and IMDG.

**14.6. Special precautions for user**

Not applicable.

**14.7. Maritime transport in bulk according to IMO instruments**

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Restrictions for application**

Restricted to professional users.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

**Demands for specific education**

No specific requirements.

**SEVESO - Categories / dangerous substances**

Not applicable.

**Additional information**

Not applicable.

**Sources**

The Health and Safety at Work etc. Act 1974 Regulations 2013.

2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

### 15.2. Chemical safety assessment

No

## SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H302, Harmful if swallowed.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H331, Toxic if inhaled.

**The full text of identified uses as mentioned in section 1**

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU 19 = Building and construction work

PROC 10 = Roller application or brushing

PC 9a = Coatings and Paints, Fillers, Putties, Thinners

ERC 8c = Wide dispersive indoor use resulting in inclusion into or onto a matrix

▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
GWP = Global warming potential  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

**Additional information**

Not applicable.

**The safety data sheet is validated by**

AG

**▼ Other**

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en