

Hardwax-oil 2K (A)



Solvent free, colorless – fast accessible – 2 component floor-oil

Characteristics

Floorservice Hardwax-oil 2K is a fast drying, quickly accessible Hardwax-oil for the professional parquet installer. Hardwax-oil 2K highlights the natural structure and color of the treated surface. High level of protection against wear and moisture influences. Resilient against staining of wine, beer, cola, coffee, tea, fruit juices, milk and water according to DIN 68861 1A standard. Hardwax-oil 2K solely contains ingredients that are conform EN71 regulations for children's toys.

Applications

to all varieties of parquet and plank flooring, to be applied as a single (1) -coat or a two (2)-coat system.

Basis

vegetable oils and waxes, drying agents and additives.

Technical data

Working temperature: not below 16°C.

Potlife: 4 hours.

Drying time: 8-12 hours (depending on room temperature and ventilation).

Chemical and mechanical accessible after 24 hours.

Physical state: liquid

Colour: colourless

Odour: characteristic

Viscosity at °C: 38-42 s 4mm

Solid content (%): 99,51 Wt %

Warning: cloths and pads containing oil should be submerged in water (risk of self combustion) before disposing via standard garbage regulations.

This product contains maximum 30 g/l VOC. EU-regulatory maximum for this product (Cat.A/e): 400g/l (2010).

Packing: 930 ml (component A), 70 ml (component B)

Instructions for use

Hardwax-oil 2K (A) stir very well before usage; add the hardener component (B) 70ml to the 930ml of component (A) and stir the mixture very well. The surface should be sanded up to grit 120, dry (humidity level of the wood not to exceed 10%) and dust / grease free.

Application with spatula: apply the oil evenly with the spatula. After 10-30 minutes remove the surplus oil with a beige pad. Apply the second layer immediately afterwards.

Coverage: 20-30ml/sqm per layer. Remove residue within 30 minutes after application by using a beige pad. After 20 minutes buff in the oil by using a white pad.

Application with a mohair roller (short haired): apply one (1) layer evenly and thin. Coverage: around 50ml/sqm depending on the wood species. After 10-30 minutes remove the surplus oil by using a spatula or rubber wiper followed by using a beige pad. After approximately 20 minutes; buff in the oil by using a white pad.

NOTICE: No surplus oil should be left on the surface!

Cleaning: Floorservice Parquet Cleaner.

Maintenance: Florservice Maintenance oil.

Above product information and recommendations are given in good faith and based on practical tests following long term research and development. We cannot assume responsibility for any work as the ultimate results depend on factors beyond our direct control. In cases of doubt always test the product in advance.

21.12.2015

OVERMAT
THE FLOOR TECHNICIANS