

MAINTENANCE AND PROTECTION FOR ALL LACQUERED PARQUET AND WOODEN FLOORS

CHARACTERISTICS

Floorservice Parquet Polish Mat protects wooden floorings, and gives the lacquer surface a matte appearance and makes the flooring water- and dirt repellent.

CONTAINS

Floorservice Parquet Polish is based on poly-acrylate dispersions.

TECHNICAL DATA

Working temperature:	10 – 25°C
Drying time:	about 60 minutes
Usage:	1 liter = approx. 60 – 80 m ²
Storage:	away from frost



SAFETY ADVICE

1,2-benzisothiazool-3(2H)-on. May cause an allergic reaction. Safety data sheet available on request.

PACKING

1 liter

INSTRUCTIONS FOR USE

Shake well.

Lacquer must be at least 3 weeks old before applying Floorservice Parquet Polish Mat. Do not use on waxed or oiled floors.

Apply undiluted product evenly over a clean and dry floor using a cloth (free of fluff), e.g. 3 to 4 times a year. Apply Parquet Polish always in the direction of the wood grain and do not rub in the opposite direction to avoid stripes.

To clean your floor (e.g. weekly) use Floorservice Parquet Cleaner. To clean your floor thoroughly and to remove build-up Polish-layers, use Floorservice Polish Remover.

IMPORTANT: Especially parquet or laminated floors are not to be wet during a longer period of time. Always pay attention to the instructions of the producer of the floor.

CLEANING & MAINTENANCE

Floorservice Parquet Cleaner and Floorservice Maintenance Oil.